

MODEL: IQ6800BDC

COOLING CAPACITY: 6824 BTU (2000W)
 HEATING CAPACITY: 2730 BTU (800W)
 OPERATING CURRENT: 16A (768W) @ 48VDC @ 95°F (35°C)
 OPERATING TEMPERATURE RANGE: -40°F TO 131°F (-40°C TO 55°C) WITH LA PACKAGE
 DIMENSIONS W/O FLANGES: 43.98" H (1117MM) X 16.42" W (417MM) X 8.86" D (225MM)
 DIMENSIONS W/ FLANGES: 46.07" H (1170MM) X 18.50" W (470MM) X 8.86" D (225MM)
 MAXIMUM SOUND LEVEL @ 5FT FROM UNIT @ A HT. OF 3FT: 60 dBA
 MAXIMUM SOUND LEVEL @ 2FT FROM UNIT @ A HT. OF 5FT: 62.8 dBA
 WEIGHT: 99.2 LBS (45KG)
 REFRIGERANT: R134a

REV	REVISION	CHG	DATE	APP	DATE	CN #
B	ADDED VERTICAL MODIFICATIONS AND CUTOUT, ADDED CFM READINGS	JWS	8/25/2021			
A	INITIAL DRAFT	NAT	9/28/2020			

ITEM NUMBER <i>N/A</i>	USED ON <i>IQ6800BDC</i>
MATERIAL <i>N/A</i>	
EST WT: lbs	
DRAWN BY <i>NAT</i>	DATE <i>9/28/2020</i>
	SCALE <i>1:12</i>

UNLESS OTHERWISE SPECIFIED TOLERANCES	
.X	±.060
.XX	±.030
.XXX	±.015
FRACTIONAL	±1/16
ANGULAR	±1/2°
SURFACE FINISH ⁶³	
DO NOT SCALE DRAWING DIMENSIONS ARE INCHES	


ICE QUBE, INC.

THIS IS A PROPRIETARY DOCUMENT. DO NOT REPRODUCE OR DISCLOSE WITHOUT THE EXPRESS WRITTEN PERMISSION OF ICE QUBE, INC.

DESCRIPTION
SPEC DRAWING

DRAWING NUMBER
IQ352499

REV
B



DIGITAL CONTROLLER

POWER AND ETHERNET CONNECTION

INSET VERTICAL MOUNT CUTOUT

VERTICAL MOUNT CUTOUT

IMPORTANT
GASKET MUST BE APPLIED AS SHOWN FOR PROPER OPERATION AND TO MAINTAIN ENCLOSURE INTEGRITY

EVAP. OUTLET ≈ 560 CFM
COND. OUTLET ≈ 615 CFM

ITEM NUMBER <i>N/A</i>	USED ON <i>IQ6800BDC</i>	UNLESS OTHERWISE SPECIFIED TOLERANCES X ±.060 .XX ±.030 .XXX ±.015 FRACTIONAL ±1/4 ANGULAR ±1/2°	<p>ICE QUBE, INC. THIS IS A PROPRIETARY DOCUMENT. DO NOT REPRODUCE OR DISCLOSE WITHOUT THE EXPRESS WRITTEN PERMISSION OF ICE QUBE, INC.</p>
MATERIAL <i>N/A</i>		<p>EST WT: lbs</p> <p>DRAWN BY: <i>NAT</i> DATE: <i>9/28/2020</i> SCALE: <i>1:12</i></p> <p>SURFACE FINISH: <i>63</i></p> <p>DO NOT SCALE DRAWING DIMENSIONS ARE INCHES</p>	
DESCRIPTION <i>SPEC RAWING</i>			DRAWING NUMBER <i>IQ352499</i>
			REV <i>B</i>