


Ordering Guide



- Sector
- Size
- Primary Feature
- Additional Feature
(Multiple Choices Permitted)
- Pattern
- Construction Materials
- End Connections
- Coatings
- Voltage-Main Valve Position
(When Solenoid De-energized)
- Tubing & Fittings
- Additional Attributes Unlimited Selection



BERMAD Ordering Guide

Hydraulic Control Valves

700 Series



Sector	Code
Waterworks	WW
Drinking Water	WD
WW Aggressive Water	WA
WW Seawater	WS
WW Air Conditioning	WC
WW Hot Water	WH

Pattern	Code
Oblique (1 1/2"-20")	Y
Angle (1 1/2"-18")	A
Globe(24-36")	G

Construction Materials	Code
Ductile Iron	C
Cast Steel	S
Stainless Steel 316	N
Nickel Aluminum Bronze	U

Other materials available on request.

Size	
1 1/2"	DN40
2"	DN50
2 1/2"	DN65
3"	DN80
4"	DN100
5"	DN125
6"	DN150
8"	DN200
10"	DN250
12"	DN300
14"	DN350
16"	DN400
18"	DN450
20"	DN500
24"	DN600
28"	DN700
30"	DN750
32"	DN800
36"	DN900


Primary Features	Code
Basic Valve (Double Chambered Actuator)	700
Basic Valve (Single Chambered Actuator)	705
Solenoid Controlled Valve	710
Electronic Control Valve	718
Pressure Management Valve, Flow Compensated PRV	7PM
Pressure Reducing Control Valve	720
Pressure Sustaining & Reducing Valve	723
Differential Pressure Reducing Valve	726
Flow Control Valve, Constant Downstream Pressure	727
Electronic Pressure Reducing Valve	728
Pressure Sustaining Valve	730
Pressure Relief Valve, Quick Type	73Q
Pressure Sustaining Valve Remote Sensing Type	730R
Surge Anticipating Valve	735
Differential Pressure Sustaining Valve	736
Electronic Pressure Sustaining Valve	738
Booster Pump Control Valve, Single Chambered Actuator	740
Booster Pump Control Valve, Double Chambered Actuator	74Q
Booster Pump Control & Pressure Reducing Valve	742
Booster Pump Control & Pressure Sustaining Valve	743
Deep Well Pump Hydraulic Control Valve	744
Deep Well Pump Electric Control Valve	745
Booster Pump & Flow Control Valve	747
Pump Circulation & Pressure Sustaining Valve	748
Pump Circulation & Flow Control Valve	749
Level Control Valve	750
Level Control & Pressure Sustaining Valve	753
Level & Flow Control Valve	757
Level Sustaining Valve (Reservoir Outlet)	75A
Hydraulic Check Valve	760
Flow Control Valve	770
Flow Control & Pressure Reducing Valve	772
Flow Control & Pressure Sustaining Valve	773
Burst Control Valve (Excessive Flow)	790
Burst Control & Pressure Reducing Valve	792
Check Valve (Lift Type)	70N
Strainer (Stone and Gravel Trap)	70F

Other primary features available on request.

Additional Features (Multiple Choices Permitted)	Code
No Additional Feature	00
Closing and Opening Speed Control	03
Differential Pressure	06
Hydraulic Override	09
Check-Lock	11
High Sensitivity Pilot	12
Electronic Control	18
Check Feature	20
Independent Flow Check (24-32" only)	2S
Solenoid Controlled & Check Feature	25
Pressure Reducing Feature	2Q
Two-Stage Opening	30
Relief Override	3Q
Electrically Selected Multi-Level Setting	45
Downstream Over Pressure Guard	48
Closing Surge Prevention	49
Motorized Pilot	4S
Electronic Multi-Level Setting - Type 4R	4R
Electronic Multi-Level Setting - Type 4T	4T
Hydraulic Control	50
Hydraulic Accelerator Control	54
Solenoid Controlled	55
Electric Override	59
Modulating Horizontal Float	60
Bi-Level Electric Float	65
Bi-Level Vertical Float	66
Modulating Vertical Float	67
Bi-Directional Flow	70
Altitude Pilot	80
Modulating Altitude Control	82
Sustaining Altitude Pilot	83
Hydraulic Positioning	85
Bi-Level Altitude Control	86
Altitude Control with Bi-Directional Flow	87
2-6 meter ; 7-20 feet Setting	M1
2-14 meter ; 7-46 feet Setting	M6
5-22 meter ; 17-72 feet Setting	M5
15-35 meter ; 49-115 feet Setting	M4
25-70 meter ; 82-230 feet Setting	M8
Closing at Downstream Pressure Drop	91
Proportional	PD

Other additional features available on request.





I6		EB		4AC		CB		F																																																																																									
<table border="1"> <thead> <tr> <th>End Connections</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td>ISO - 10</td> <td>10</td> </tr> <tr> <td>ISO - 16</td> <td>16</td> </tr> <tr> <td>ISO - 25</td> <td>25</td> </tr> <tr> <td>ANSI - 150</td> <td>A5</td> </tr> <tr> <td>ANSI - 300</td> <td>A3</td> </tr> <tr> <td>BST - D</td> <td>BD</td> </tr> <tr> <td>JIS - 16</td> <td>J6</td> </tr> <tr> <td>JIS - 20</td> <td>J2</td> </tr> <tr> <td>BSP</td> <td>BP</td> </tr> <tr> <td>BSP - 25 bar</td> <td>PH</td> </tr> <tr> <td>NPT</td> <td>NP</td> </tr> <tr> <td>NPT - 25 bar</td> <td>NH</td> </tr> </tbody> </table> <p>Other end connections available on request.</p>		End Connections	Code	ISO - 10	10	ISO - 16	16	ISO - 25	25	ANSI - 150	A5	ANSI - 300	A3	BST - D	BD	JIS - 16	J6	JIS - 20	J2	BSP	BP	BSP - 25 bar	PH	NPT	NP	NPT - 25 bar	NH	<table border="1"> <thead> <tr> <th>Voltage-Main Valve Position (When Solenoid De-energized)</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td rowspan="6">24V</td> <td rowspan="3">AC</td> <td>24VAC/50Hz - Normally Closed</td> <td>4AC</td> </tr> <tr> <td>24VAC/50Hz - Normally Open</td> <td>4AO</td> </tr> <tr> <td>24VAC/50Hz - Last Position</td> <td>4AP</td> </tr> <tr> <td rowspan="3">DC</td> <td>24VAC/60Hz - Normally Closed</td> <td>46C</td> </tr> <tr> <td>24VAC/60Hz - Normally Open</td> <td>46O</td> </tr> <tr> <td>24VAC/60Hz - Last Position</td> <td>46P</td> </tr> <tr> <td rowspan="6">220V</td> <td rowspan="3">AC</td> <td>24VDC - Normally Closed</td> <td>4DC</td> </tr> <tr> <td>24VDC - Normally Open</td> <td>4DO</td> </tr> <tr> <td>24VDC - Last Position</td> <td>4DP</td> </tr> <tr> <td rowspan="3">DC</td> <td>24VDC - Latch Solenoid</td> <td>4DS</td> </tr> <tr> <td>220VAC/50-60Hz Last Position</td> <td>2AP</td> </tr> <tr> <td>220VAC/50-60Hz Normally Closed</td> <td>2AC</td> </tr> <tr> <td rowspan="6">110V</td> <td rowspan="3">AC</td> <td>220VAC/50-60Hz Normally Open</td> <td>2AO</td> </tr> <tr> <td>220VAC/50-60Hz Motorized Ball Valve - Last Position</td> <td>2AM</td> </tr> <tr> <td>220VDC - Normally Closed</td> <td>2DC</td> </tr> <tr> <td rowspan="3">DC</td> <td>220VDC - Normally Open</td> <td>2DO</td> </tr> <tr> <td>220VDC - Latch Solenoid</td> <td>2DS</td> </tr> <tr> <td>110VAC/50 - 60Hz Normally Closed</td> <td>5AC</td> </tr> <tr> <td rowspan="4">DC</td> <td>110VAC/50 - 60Hz Normally Open</td> <td>5AO</td> </tr> <tr> <td>110VDC - Normally Closed</td> <td>5DC</td> </tr> <tr> <td>110VDC - Normally Open</td> <td>5DO</td> </tr> <tr> <td>110VDC - Latch Solenoid</td> <td>5DS</td> </tr> </tbody> </table> <p>Other electrical ratings available on request.</p>		Voltage-Main Valve Position (When Solenoid De-energized)	Code	24V	AC	24VAC/50Hz - Normally Closed	4AC	24VAC/50Hz - Normally Open	4AO	24VAC/50Hz - Last Position	4AP	DC	24VAC/60Hz - Normally Closed	46C	24VAC/60Hz - Normally Open	46O	24VAC/60Hz - Last Position	46P	220V	AC	24VDC - Normally Closed	4DC	24VDC - Normally Open	4DO	24VDC - Last Position	4DP	DC	24VDC - Latch Solenoid	4DS	220VAC/50-60Hz Last Position	2AP	220VAC/50-60Hz Normally Closed	2AC	110V	AC	220VAC/50-60Hz Normally Open	2AO	220VAC/50-60Hz Motorized Ball Valve - Last Position	2AM	220VDC - Normally Closed	2DC	DC	220VDC - Normally Open	2DO	220VDC - Latch Solenoid	2DS	110VAC/50 - 60Hz Normally Closed	5AC	DC	110VAC/50 - 60Hz Normally Open	5AO	110VDC - Normally Closed	5DC	110VDC - Normally Open	5DO	110VDC - Latch Solenoid	5DS	<table border="1"> <thead> <tr> <th>Tubing & Fittings</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td>St. St. 316 Tubing & Fittings</td> <td>NN</td> </tr> <tr> <td>Copper Tubing & Brass Fittings</td> <td>CB</td> </tr> <tr> <td>Plastic Reinforced Tubing & Brass Fittings</td> <td>PB</td> </tr> <tr> <td>Monel Tubing & Fittings</td> <td>MM</td> </tr> </tbody> </table>		Tubing & Fittings	Code	St. St. 316 Tubing & Fittings	NN	Copper Tubing & Brass Fittings	CB	Plastic Reinforced Tubing & Brass Fittings	PB	Monel Tubing & Fittings	MM
End Connections	Code																																																																																																
ISO - 10	10																																																																																																
ISO - 16	16																																																																																																
ISO - 25	25																																																																																																
ANSI - 150	A5																																																																																																
ANSI - 300	A3																																																																																																
BST - D	BD																																																																																																
JIS - 16	J6																																																																																																
JIS - 20	J2																																																																																																
BSP	BP																																																																																																
BSP - 25 bar	PH																																																																																																
NPT	NP																																																																																																
NPT - 25 bar	NH																																																																																																
Voltage-Main Valve Position (When Solenoid De-energized)	Code																																																																																																
24V	AC	24VAC/50Hz - Normally Closed	4AC																																																																																														
		24VAC/50Hz - Normally Open	4AO																																																																																														
		24VAC/50Hz - Last Position	4AP																																																																																														
	DC	24VAC/60Hz - Normally Closed	46C																																																																																														
		24VAC/60Hz - Normally Open	46O																																																																																														
		24VAC/60Hz - Last Position	46P																																																																																														
220V	AC	24VDC - Normally Closed	4DC																																																																																														
		24VDC - Normally Open	4DO																																																																																														
		24VDC - Last Position	4DP																																																																																														
	DC	24VDC - Latch Solenoid	4DS																																																																																														
		220VAC/50-60Hz Last Position	2AP																																																																																														
		220VAC/50-60Hz Normally Closed	2AC																																																																																														
110V	AC	220VAC/50-60Hz Normally Open	2AO																																																																																														
		220VAC/50-60Hz Motorized Ball Valve - Last Position	2AM																																																																																														
		220VDC - Normally Closed	2DC																																																																																														
	DC	220VDC - Normally Open	2DO																																																																																														
		220VDC - Latch Solenoid	2DS																																																																																														
		110VAC/50 - 60Hz Normally Closed	5AC																																																																																														
DC	110VAC/50 - 60Hz Normally Open	5AO																																																																																															
	110VDC - Normally Closed	5DC																																																																																															
	110VDC - Normally Open	5DO																																																																																															
	110VDC - Latch Solenoid	5DS																																																																																															
Tubing & Fittings	Code																																																																																																
St. St. 316 Tubing & Fittings	NN																																																																																																
Copper Tubing & Brass Fittings	CB																																																																																																
Plastic Reinforced Tubing & Brass Fittings	PB																																																																																																
Monel Tubing & Fittings	MM																																																																																																

Reduction Ratios Table

Valve Size	Plug Type	
	Flat Disk	V-Port
1 1/2 - 2 1/2" DN40 - 65	3.7	4
3" DN80	2.6	2.9
4" DN100	2.5	2.8
6" DN150	2.5	2.7
8" DN200	2.4	2.6
10" DN250	2.3	2.5
12-14" DN300 - 350	2.2	2.4
16-20" DN400 - 500	2.2	2.3
24-36" DN600 - 900	2.2	2.3

- The reduction ratios are based on flow velocity of 2.0-3.0 m/sec.
- Reduction ratio may vary at extreme flow velocity & upstream pressure.

Coatings	Code
Epoxy FB Blue RAL 5005	EB
Polyester Green RAL 6017	PG
Polyester Blue RAL 5010	PB
Uncoated	UC

Transparent Polyurethane top coating is available for epoxy coated valves. Other coatings available on request.

Additional Attributes Unlimited Selection	Code
V-Port Throttling Plug (U-Type)	V
Large Control Filter	F
Valve Position Indicator	I
Electric Limit Switch	S
Valve Position Transmitter	Q
Flow Stem	M
Lifting Spring	L
Balancing Piston Assembly	G
Orifice Assembly	U
Pressure Separator	d
Double Chambered (Active)	B
3-Way Control Loop	X
Manual Selector	Z
Flow Over the Seat	O
St. St. 316 Control Accessories	N
St. St. 316 Actuator Internal Assembly	D
St. St. 316 Internal Trim (Closure & Seat)	T
Delrin Bearing	R
High Grade Bearing & Stem	K
St. St. Bolts & Nuts	m
Special Elastomers for Seals & Diaphragm	E
Pressure Gauge	6

Other additional attributes are optional. Please consult our sales department for further information.

Ordering Guide

BERMAD Ordering Guide

Hydraulic Control Valves

700 Series



info@bermad.com • www.bermad.com

The information herein is subject to change without notice. BERMAD shall not be held liable for any errors. All rights reserved.
© Copyright by BERMAD.

P07WE01 09