

| | | |
|----------|---------------------------|---|
| | Size In. | 6" |
| | Strainer Type | Y = Y Strainer |
| | Class | 125 = 125 lb. 150 = 150 lb. 250 = 250 lb. 300 = 300 lb. 600 = 600 lb. 900 = 900 lb. 1500 = 1500 lb. |
| | Type of Connection | T = NPT Threaded SW = Socket Weld S = Sweat End F = Flanged (RF or FF depending on standard of construction) BW = Buttweld RTJ = Ring Joint |
| | Body Material | I = A126-B Cast Iron DI = A395 Ductile Iron B = B62 Bronze S = A216-WCB Carbon Steel LCB = A352-LCB Steel LCC = A352-LCC Steel 52CM = A217-WC6 Chrome Molly 94CM = A217-WC9 Chrome Molly SS = A351-CF8M Stainless Steel A20 = A351-CN7M Alloy 20 |
| | Cover Type | T = Threaded cover B = Bolted cover |
| | Specials/Other | 1 = Non-standard screen 2 = Non-standard gasket 3 = Special external coating 4 = Special internal coating 5 = Oxygen Service 6 = NACE MR01-75 Compliance 7 = Silicon Free 8 = Special N.D.E. 9 = Other Special |
| A | | |
| B | | |
| C | | |
| D | | |
| E | | |
| F | | |
| G | | |